http://www.jourmag.org/index.php/jma

Journal of Magnetism and Its Applications

Received January 21th 2025 received in revised April 9th 2025 accepted April 11th 2025

Research articles

Two-Dimensional Magnetic Materials and Their Applications in Spintronic Devices

Michael Anderson
Department of Electrical Engineering, Massachusetts Institute of Technology (MIT), Cambridge, USA

Article info

Keywords:
Two-dimensional materials,
Spintronics,
Magnetic thin films,
Ferromagnetism,
Magnetic anisotropy,
Spin transport,
Magnetic tunnel junctions,
Quantum materials

Abstract

Two-dimensional (2D) magnetic materials have recently emerged as an exciting class of materials for next-generation spintronic devices. Unlike conventional electronic devices that rely on electron charge, spintronics exploits the spin degree of freedom of electrons to enable faster, more energy-efficient, and non-volatile information processing technologies. The discovery of intrinsic ferromagnetism in atomically thin materials such as CrI_3, $Cr_2Ge_2Te_6$, and Fe_3GeTe_2 has opened new opportunities for integrating magnetic functionality into nanoscale electronic devices. These materials exhibit unique magnetic, electronic, and optical properties that can be tuned through strain, doping, and external fields. This article reviews the fundamental properties of two-dimensional magnetic materials, their synthesis methods, and their potential applications in spintronic devices including magnetic tunnel junctions, spin filters, and memory systems. The study also discusses current challenges such as material stability, fabrication scalability, and interface engineering. Finally, future prospects of 2D magnetism in quantum technologies and energy-efficient electronics are highlighted.

Introduction

Spintronics, or spin-based electronics, represents a transformative approach in modern electronics by utilizing the intrinsic spin of electrons in addition to their charge. Traditional semiconductor devices rely solely on charge transport, which leads to significant energy losses and thermal limitations as devices scale down. In contrast, spintronic technologies promise improved energy efficiency, faster switching speeds, and enhanced data storage capabilities. The discovery of two-dimensional materials such as graphene has significantly expanded research in low-dimensional systems. However, graphene itself lacks intrinsic magnetism, limiting its application in magnetic technologies. Recently, the discovery of intrinsic ferromagnetism in atomically thin materials such as chromium triiodide (CrI_3) and chromium germanium telluride ($Cr_2Ge_2Te_6$) has opened a new frontier in condensed matter physics and materials science. Two-dimensional magnetic materials possess unique properties that differ from bulk magnetic materials due to reduced dimensionality, quantum confinement effects, and strong spin–orbit coupling. These properties make them highly promising for applications in spin-based electronics and quantum devices. Researchers are actively exploring methods to integrate these materials into functional spintronic architectures. Their atomically thin structure allows seamless integration with semiconductor platforms, enabling the development of ultra-compact and energy-efficient electronic systems.

Fundamental Properties of Two-Dimensional Magnetic Materials

Two-dimensional (2D) magnetic materials possess distinctive physical and magnetic characteristics that arise from their atomic-scale thickness and reduced dimensionality. In these materials, magnetic ordering is strongly influenced by exchange interactions between neighboring atomic spins and the presence of magnetic anisotropy. Exchange interactions determine whether spins align parallel or antiparallel, leading to ferromagnetic or antiferromagnetic ordering. However, according to the Mermin–Wagner theorem, long-range magnetic order in strictly two-dimensional systems cannot exist at finite temperatures without the presence of anisotropy. Magnetic anisotropy introduces an energy barrier that stabilizes spin alignment and allows magnetic ordering to persist even in ultrathin layers. The discovery of intrinsic ferromagnetism in van der Waals layered materials has revolutionized the field of low-dimensional magnetism. Materials such as chromium triiodide (CrI_3), chromium germanium telluride ($Cr_2Ge_2Te_6$), and iron germanium telluride (Fe_3GeTe_2) exhibit stable magnetic ordering even when reduced to monolayer thickness. Among these, Fe_3GeTe_2 is particularly notable because it demonstrates relatively high Curie temperatures compared to many other 2D magnetic materials. This property makes it a promising candidate for spintronic devices that require stable magnetic behavior under practical operating conditions. Another important feature of two-dimensional magnetic materials is their strong spin–orbit coupling and magnetocrystalline anisotropy. These properties influence how spins interact with the crystal lattice and external magnetic fields. Strong spin–orbit coupling can lead to phenomena such as the anomalous Hall effect, spin–orbit torque, and topological magnetic states, all of which are highly relevant for advanced spintronic applications. These effects allow researchers to manipulate electron spin states using electrical signals rather than external magnetic fields, enabling more energy-efficient device operation. The tunability of magnetic properties is one of the most attractive characteristics of 2D magnetic materials. Their thin structure allows external stimuli such as electric fields, mechanical strain, pressure, or chemical doping to significantly modify their magnetic behavior. For instance, applying an electric field can alter magnetic anisotropy, enabling electrical control of magnetization states. Similarly, strain engineering can change interatomic distances within the crystal lattice, thereby modifying exchange interactions and magnetic ordering temperatures. Furthermore, the ability to stack different two-dimensional materials into van der Waals heterostructures enables the creation of artificial magnetic systems with tailored properties. By combining magnetic layers with nonmagnetic materials such as graphene or transition metal dichalcogenides, researchers can design structures with enhanced spin transport and controlled magnetic interactions. These heterostructures offer a versatile platform for studying fundamental quantum phenomena and developing novel spin-based technologies.

Synthesis and Fabrication Techniques

The fabrication of high-quality two-dimensional magnetic materials is essential for both fundamental research and practical device applications. Because the magnetic properties of these materials are highly sensitive to structural defects, impurities, and thickness variations, precise synthesis techniques are required to achieve uniform and stable atomic layers. Over the past decade, several fabrication approaches have been developed to produce 2D magnetic materials with controlled thickness, crystallinity, and chemical composition. One of the earliest and most widely used techniques is mechanical exfoliation, which involves peeling thin layers from bulk crystals using adhesive tape or other mechanical methods. This approach was first popularized during the discovery of graphene and has since been applied to many layered materials. Mechanical

*Corresponding author
Email: manderson@mit.edu
DOI: 10.53533/JMA.v2i1.27

exfoliation can produce extremely high-quality monolayers with minimal defects, making it ideal for laboratory studies. However, the method is limited in scalability and reproducibility, which restricts its use for large-scale industrial manufacturing. To address these limitations, researchers have turned to chemical vapor deposition (CVD) as a scalable synthesis technique. In CVD processes, gaseous precursor molecules react at high temperatures on a substrate surface to form thin crystalline layers. This technique allows precise control over growth conditions such as temperature, pressure, and gas flow rates, enabling the production of large-area films with uniform thickness. CVD is widely considered one of the most promising methods for manufacturing 2D materials for electronic and spintronic applications. Another advanced technique used for fabricating ultrathin magnetic materials is molecular beam epitaxy (MBE). MBE is a highly controlled vacuum-based deposition method that enables atomic-level precision in thin-film growth. In this process, beams of atoms or molecules are directed toward a heated substrate, where they condense to form crystalline layers. Because MBE allows extremely precise control over composition and layer thickness, it is particularly useful for studying fundamental physical properties and constructing complex heterostructures. In addition to these synthesis techniques, modern nanofabrication and lithography technologies play a crucial role in integrating two-dimensional magnetic materials into functional devices. Techniques such as electron-beam lithography, focused ion beam processing, and atomic layer deposition allow researchers to pattern nanoscale structures and fabricate spintronic circuits. These fabrication methods enable the creation of magnetic tunnel junctions, spin valves, and other nanoscale devices required for advanced spin-based electronics. Encapsulation and protective coatings are also important considerations in the fabrication process. Many 2D magnetic materials are sensitive to environmental factors such as oxygen and moisture, which can degrade their magnetic properties. To address this issue, researchers often encapsulate these materials between layers of inert materials such as hexagonal boron nitride (h-BN). This protective strategy preserves the structural integrity and magnetic performance of the materials during device operation.

Applications in Spintronic Devices

Two-dimensional magnetic materials have opened new possibilities for the development of next-generation spintronic technologies. Spintronics, which utilizes the spin state of electrons in addition to their charge, offers significant advantages over traditional electronics, including lower power consumption, faster switching speeds, and non-volatile memory operation. The atomic-scale thickness and tunable magnetic properties of 2D magnetic materials make them particularly attractive for integration into nanoscale spintronic devices. One of the most important applications of these materials is in magnetic tunnel junctions (MTJs). An MTJ typically consists of two magnetic layers separated by a thin insulating barrier. When electrons tunnel through the barrier, the resistance of the device depends on the relative orientation of the magnetizations in the two magnetic layers. This phenomenon, known as tunneling magnetoresistance (TMR), forms the basis of modern magnetic memory technologies such as magnetic random-access memory (MRAM). The use of two-dimensional magnets in MTJs can significantly reduce device size while improving switching efficiency. Another promising application involves spin-filter devices, which exploit the spin-selective transport properties of magnetic materials. In these devices, a magnetic layer acts as a filter that allows electrons with one spin orientation to pass while blocking electrons with the opposite spin. This selective transport enables efficient generation and detection of spin-polarized currents, which are essential for many spintronic circuits and quantum computing applications. Two-dimensional magnetic materials also play a key role in spin–orbit torque devices, where electrical currents are used to manipulate magnetic states through spin–orbit interactions. This mechanism allows rapid and energy-efficient switching of magnetic bits without the need for external magnetic fields. Such technologies are expected to play an important role in the development of next-generation memory and logic devices. In addition to memory applications, 2D magnetic materials are being explored for spin-based logic circuits. Unlike conventional logic circuits that rely on charge transport, spin logic devices use spin states to perform computational operations. This approach can potentially reduce power consumption and enable highly parallel information processing systems. Furthermore, hybrid structures combining two-dimensional magnets with semiconductors, superconductors, or topological materials are opening new research directions. These hybrid systems enable the study of exotic quantum phenomena such as spin Hall effects, topological magnetism, and Majorana fermions. Such discoveries could lead to revolutionary technologies in quantum information processing and neuromorphic computing. Overall, the integration of two-dimensional magnetic materials into spintronic architectures represents a significant step toward the development of ultra-efficient electronic systems. Continued advances in material synthesis, device engineering, and theoretical understanding will further accelerate the adoption of these materials in practical technological applications.

Challenges and Future Research Directions

Despite remarkable advances in the study of two-dimensional magnetic materials, several scientific and technological challenges continue to hinder their widespread implementation in practical spintronic devices. One of the most significant limitations is the relatively low Curie temperature (Tc) observed in many 2D magnetic systems. The Curie temperature represents the threshold above which a ferromagnetic material loses its magnetic ordering. Many currently studied two-dimensional magnets, such as CrI_3 and $Cr_2Ge_2Te_6$, exhibit Curie temperatures well below room temperature. This restricts their direct application in commercial electronics, which typically require stable magnetic properties under ambient operating conditions. Consequently, one of the central goals of current research is to design materials that retain robust magnetic ordering at or above room temperature. Another important challenge relates to the environmental stability of two-dimensional magnetic materials. Many of these materials are highly sensitive to atmospheric conditions, particularly oxygen and moisture. Exposure to air can lead to chemical degradation, oxidation, or structural changes that significantly alter their magnetic properties. This instability complicates device fabrication and long-term reliability. To address this issue, researchers are developing protective strategies such as encapsulating 2D magnets within chemically inert materials like hexagonal boron nitride (h-BN). Such encapsulation techniques protect the material from environmental damage while preserving its electronic and magnetic characteristics. In addition, chemical modifications and alloy engineering are being explored to improve intrinsic stability. The scalability of fabrication techniques also remains a major barrier to commercialization. Many experimental studies rely on mechanical exfoliation methods that produce small, irregular flakes of material. Although these samples are ideal for fundamental research, they are unsuitable for large-scale device manufacturing. To overcome this limitation, researchers are investigating scalable growth techniques such as chemical vapor deposition (CVD), molecular beam epitaxy (MBE), and atomic layer deposition. These methods allow for the controlled synthesis of large-area thin films with uniform thickness and crystal quality. Achieving reliable and reproducible fabrication at industrial scales is essential for integrating two-dimensional magnetic materials into practical electronic and spintronic systems. Another challenge arises from the complexity of interfaces in multilayer device structures. Spintronic devices often require stacking multiple materials with different electronic and magnetic properties. Imperfections at the interfaces between layers can significantly affect spin transport efficiency, magnetic coupling, and overall device performance. Therefore, precise control of interfacial properties is critical. Researchers are currently exploring van der Waals heterostructures, where atomically thin layers are stacked without strong chemical bonding. These heterostructures provide clean interfaces and enable novel magnetic interactions that can enhance device functionality. Thermal management and spin transport efficiency are additional factors that require further investigation. In nanoscale devices, heat generation and dissipation can strongly influence magnetic behavior and device reliability. Understanding how spin currents propagate through two-dimensional materials and across interfaces is essential for optimizing device performance. Advanced characterization techniques, including spin-polarized scanning tunneling microscopy and ultrafast spectroscopy, are helping researchers explore these processes in greater detail. Looking toward the future, one of the most promising research directions is the discovery of new two-dimensional magnetic materials with improved magnetic transition temperatures and enhanced stability. The rapid expansion of computational materials science is playing a key role in this effort. Machine learning algorithms and high-throughput computational screening are being used to analyze large materials databases and predict candidate materials with desirable magnetic and electronic properties. This approach significantly accelerates the discovery process compared to traditional experimental trial-and-error methods. Another emerging research area involves the development of hybrid quantum materials and multifunctional heterostructures. By combining 2D magnets with other advanced materials such as topological insulators, superconductors, and semiconductors, researchers can create systems with novel quantum phenomena. These hybrid structures may enable breakthroughs in quantum information processing, spin-based logic devices, and neuromorphic computing architectures. Furthermore, future research will likely focus on electric-field

control of magnetism, which could allow spintronic devices to operate with extremely low power consumption. The ability to manipulate magnetic states using electric fields rather than magnetic fields represents a significant technological advantage and could lead to the development of ultra-efficient memory and logic devices. In summary, while two-dimensional magnetic materials offer tremendous potential for next-generation spintronic technologies, several fundamental and engineering challenges remain. Addressing issues related to Curie temperature, environmental stability, fabrication scalability, and interface control will be essential for translating laboratory discoveries into real-world applications. Continued collaboration between materials scientists, physicists, and device engineers will play a critical role in advancing this rapidly evolving field.

Summary

Two-dimensional magnetic materials represent a major advancement in materials science and condensed matter physics. Their unique magnetic properties and atomic-scale thickness make them promising candidates for next-generation spintronic devices. These materials enable efficient spin manipulation, reduced power consumption, and improved device miniaturization. Although several challenges remain in terms of stability, fabrication scalability, and operating temperature, ongoing research continues to address these limitations. With continued progress in material synthesis and device engineering, two-dimensional magnets are expected to play a critical role in the development of future electronic, quantum, and information technologies.

References

[1] Gong, C., & Zhang, X. (2019). Two-dimensional magnetic crystals and emergent heterostructure devices. Science, 363(6428), eaav4450.
[2] Huang, B., Clark, G., Navarro-Moratalla, E., et al. (2017). Layer-dependent ferromagnetism in a van der Waals crystal down to the monolayer limit. Nature, 546, 270–273.
[3] Burch, K. S., Mandrus, D., & Park, J. G. (2018). Magnetism in two-dimensional van der Waals materials. Nature, 563, 47–52.
[4] Gibertini, M., Koperski, M., Morpurgo, A. F., & Novoselov, K. (2019). Magnetic 2D materials and heterostructures. Nature Nanotechnology, 14, 408–419.
[5] Bonilla, M., Kolekar, S., Ma, Y., et al. (2018). Strong room-temperature ferromagnetism in VSe_2 monolayers. Nature Nanotechnology, 13, 289–293.
[6] Jiang, S., Shan, J., & Mak, K. F. (2018). Electric-field switching of two-dimensional van der Waals magnets. Nature Materials, 17, 406–410.
[7] Song, T., Cai, X., Tu, M. W., et al. (2018). Giant tunneling magnetoresistance in layered magnetic semiconductor CrI_3. Science, 360, 1214–1218.
[8] Baltz, V., Manchon, A., Tsoi, M., et al. (2018). Antiferromagnetic spintronics. Reviews of Modern Physics, 90, 015005.
[9] Wang, H., Fan, F., Zhu, S., & Wu, H. (2020). Doping-induced magnetism in two-dimensional materials. Journal of Materials Chemistry C, 8, 8051–8060.
[10] Zhang, W., Wu, Q., Wang, Z., et al. (2020). Magnetic van der Waals materials for spintronic devices. Advanced Materials, 32, 2003311.
[11] Deng, Y., Yu, Y., Song, Y., et al. (2018). Gate-tunable room-temperature ferromagnetism in two-dimensional Fe_3GeTe_2. Nature, 563, 94–99.
[12] Mak, K. F., & Shan, J. (2016). Photonics and optoelectronics of 2D semiconductor materials. Nature Photonics, 10, 216–226.