http://www.jourmag.org/index.php/jma

Journal of Magnetism and Its Applications

Received December 20nd 2022; received in revised December 26th 2022; accepted December 27th 2022

Research articles

Multiferroic Materials and Their Role in Magnetoelectric Devices

Carlos Mendes

Institute for Nanotechnology and Advanced Materials, University of Lisbon, Lisbon, Portugal

Article info

Keywords:
Multiferroics, Magnetoelectric coupling, Spintronics, Ferroelectric materials, Magnetic materials, Functional nanomaterials, Magnetoelectric devices, Smart materials

Abstract

Multiferroic materials, which simultaneously exhibit more than one ferroic property such as ferromagnetism, ferroelectricity, and ferroelasticity, have attracted significant attention due to their potential applications in next-generation electronic and spintronic devices. Among these materials, magnetoelectric multiferroics are particularly important because they enable the coupling between electric and magnetic order parameters. This coupling allows electric fields to control magnetic states and vice versa, creating new opportunities for energy-efficient memory, sensing, and communication technologies. The development of magnetoelectric devices based on multiferroic materials offers promising solutions for reducing power consumption in modern electronic systems. However, challenges such as weak coupling strength, low operating temperatures, and fabrication limitations still hinder large-scale applications. This article reviews the fundamental properties of multiferroic materials, their classification, mechanisms of magnetoelectric coupling, fabrication approaches, and their emerging applications in magnetoelectric devices. The study also highlights current research trends and technological prospects in the development of advanced multifunctional materials for future electronic systems.

1. Introduction

Multiferroic materials represent an important class of functional materials that exhibit two or more ferroic properties simultaneously, such as ferromagnetism, ferroelectricity, and ferroelasticity. These materials have gained increasing attention in condensed matter physics and materials science because they enable the interaction between electric and magnetic properties within a single material system. The coexistence of magnetic and electric order parameters allows for the development of magnetoelectric coupling mechanisms. In such systems, magnetic properties can be controlled by an external electric field, while electric polarization can be manipulated using magnetic fields. This dual functionality provides unique opportunities for designing highly efficient electronic devices. Traditional electronic devices rely heavily on charge-based mechanisms, which often lead to high energy consumption and thermal losses. In contrast, magnetoelectric devices based on multiferroic materials offer energy-efficient alternatives by utilizing spin and polarization states for information storage and processing. Recent advances in nanotechnology, thin-film fabrication, and material engineering have accelerated research in multiferroic materials. Scientists are exploring various material systems, including perovskite oxides, composite heterostructures, and layered nanostructures, to enhance magnetoelectric coupling and improve device performance. The growing interest in multiferroic materials is also driven by their potential applications in emerging technologies such as spintronics, non-volatile memory systems, sensors, and energy-efficient logic devices. Understanding the fundamental physics and engineering challenges associated with these materials is essential for their successful integration into practical technologies.

Classification of Multiferroic Materials

Multiferroic materials are typically classified according to the origin and interaction of their ferroic properties, particularly ferroelectricity and magnetism. This classification helps researchers understand the mechanisms governing these materials and their suitability for various technological applications. The two primary categories are Type-I multiferroics and Type-II multiferroics, although composite multiferroic systems are also widely studied due to their enhanced magnetoelectric performance. Type-I multiferroics, also known as proper multiferroics, exhibit ferroelectric and magnetic ordering that arise from independent physical mechanisms within the crystal structure. In these materials, the electric polarization and magnetic ordering occur due to different structural or electronic processes. Because of this independence, Type-I multiferroics often demonstrate strong ferroelectric polarization but relatively weak magnetoelectric coupling. Despite the weak coupling between the two ferroic orders, these materials are valuable due to their relatively high transition temperatures and structural stability. One of the most well-known examples of a Type-I multiferroic material is bismuth ferrite ($BiFeO_3$). This material is particularly significant because it exhibits both ferroelectric and antiferromagnetic ordering at room temperature, making it one of the few multiferroics suitable for practical device applications. The crystal structure of $BiFeO_3$ belongs to the perovskite family, which is widely studied in functional materials research due to its versatile electronic and magnetic properties. Other examples of Type-I multiferroics include $YMnO_3$ and $LuFeO_3$, which also demonstrate strong ferroelectric characteristics. In contrast, Type-II multiferroics, often referred to as improper multiferroics, display ferroelectricity that originates directly from magnetic ordering. In these materials, the electric polarization is induced by complex magnetic interactions, such as spiral spin structures or non-collinear magnetic arrangements. As a result, Type-II multiferroics typically exhibit stronger magnetoelectric coupling compared to Type-I materials. However, their ferroelectric polarization is usually weaker, and their transition temperatures are often lower, which can limit their practical applications. Examples of Type-II multiferroics include materials such as $TbMnO_3$, $DyMnO_3$, and $Ni_3V_2O_8$. These materials exhibit ferroelectric behavior only when specific magnetic ordering occurs. In $TbMnO_3$, for instance, the formation of a spiral magnetic structure breaks spatial inversion symmetry, which generates electric polarization through spin-driven mechanisms. Such magnetically induced ferroelectricity provides an effective pathway for controlling electric polarization using magnetic fields. Another important class of multiferroic systems is composite multiferroic materials, which are engineered structures combining separate ferroelectric and ferromagnetic phases. These materials are designed to overcome the limitations found in single-phase multiferroics by enhancing magnetoelectric coupling through mechanical interactions. In composite systems, magnetoelectric coupling is typically achieved through strain-mediated mechanisms, where magnetostrictive materials respond to magnetic fields by deforming mechanically. This deformation then influences the ferroelectric component, resulting in a change in electric polarization. Composite multiferroics are often

*Corresponding author
Email: carlos.mendes@ulisboa.pt
DOI: 10.53533/JMA.v2i1.27

fabricated as layered heterostructures, nanocomposites, or thin-film multilayers. Common combinations include $CoFe_2O_4$–$BaTiO_3$ and Terfenol-D–PZT systems. These hybrid materials can produce significantly stronger magnetoelectric effects than single-phase multiferroics, making them promising candidates for practical applications in sensors, actuators, and energy-efficient electronic devices.

Mechanisms of Magnetoelectric Coupling

Magnetoelectric coupling is the key phenomenon that allows electric and magnetic properties to interact in multiferroic materials. This coupling enables the control of magnetic states using electric fields and the manipulation of electric polarization using magnetic fields. Such functionality is highly desirable for the development of advanced electronic devices, particularly those aimed at reducing power consumption and improving operational efficiency. One of the fundamental mechanisms responsible for magnetoelectric coupling is the spin–lattice interaction. In this mechanism, magnetic ordering influences the atomic lattice structure of the material. Changes in the orientation of magnetic moments can lead to distortions in the crystal lattice, which in turn generate electric polarization. This coupling between magnetic spin states and lattice vibrations plays a significant role in many magnetically driven multiferroic materials. Another important mechanism is exchange striction, which arises from variations in magnetic exchange interactions between neighboring atoms. When the magnetic alignment between atoms changes, it can cause local lattice distortions. These distortions lead to the displacement of ions within the crystal structure, generating electric dipoles and producing ferroelectric polarization. Exchange striction is particularly significant in materials with non-collinear magnetic structures, where magnetic interactions strongly influence lattice dynamics. In addition to these intrinsic mechanisms, spin-orbit coupling can also contribute to magnetoelectric interactions. Spin-orbit coupling links the spin of electrons with their orbital motion around atomic nuclei, creating a pathway through which magnetic order can influence electric polarization. This effect is especially important in materials with strong relativistic interactions and complex magnetic ordering patterns. In composite multiferroic systems, magnetoelectric coupling is often achieved through strain-mediated interactions. In such systems, the magnetostrictive component changes its shape when exposed to a magnetic field. This mechanical deformation is transferred to the adjacent ferroelectric layer, altering its electric polarization. Conversely, an applied electric field can induce strain in the ferroelectric component, which then affects the magnetic properties of the magnetostrictive phase. The efficiency of magnetoelectric devices depends heavily on the strength of this coupling. Strong magnetoelectric coupling allows more effective control of magnetic states using electric fields, which is crucial for the development of low-power memory and logic devices. Researchers are therefore focusing on discovering new materials with stronger intrinsic coupling and designing nanostructured composite systems that enhance interfacial interactions. Recent advances in nanotechnology and materials engineering have opened new opportunities for improving magnetoelectric coupling. Techniques such as interface engineering, thin-film growth, and strain tuning are being used to manipulate the interaction between electric and magnetic order parameters at the nanoscale. These approaches are expected to significantly enhance the performance of future magnetoelectric devices. Overall, understanding the mechanisms that govern magnetoelectric coupling is essential for the development of next-generation multifunctional materials. Continued research in this area will contribute to the design of innovative technologies in fields such as spintronics, energy-efficient computing, magnetic sensing, and advanced memory systems.

Fabrication Techniques for Multiferroic Materials

The fabrication of multiferroic materials requires careful control over crystal structure, chemical composition, and microstructural properties in order to achieve stable ferroelectric and magnetic behavior simultaneously. Because the coexistence of these properties is often sensitive to defects, grain boundaries, and compositional variations, advanced synthesis techniques are employed to ensure high material quality. Over the past few decades, researchers have developed several thin-film deposition and bulk fabrication methods that enable precise engineering of multiferroic materials for electronic and magnetoelectric applications. One of the most widely used fabrication approaches is sol–gel processing, a chemical synthesis technique that enables the preparation of multiferroic thin films and nanostructured materials with controlled composition. In this process, metal alkoxides or inorganic salts are dissolved in a solution to form a homogeneous precursor. Through hydrolysis and condensation reactions, the solution gradually transforms into a gel-like network. Subsequent drying and heat treatment convert the gel into a crystalline oxide material. Sol–gel methods are particularly advantageous because they allow precise stoichiometric control, relatively low processing temperatures, and cost-effective large-scale production. This technique is commonly used for fabricating materials such as $BiFeO_3$ thin films, which are widely studied in multiferroic research. Another important technique for synthesizing high-quality multiferroic thin films is pulsed laser deposition (PLD). In PLD, a high-energy laser beam is directed onto a target material, causing the material to ablate and form a plasma plume that deposits onto a heated substrate. This process enables the growth of epitaxial thin films with excellent crystalline quality and well-defined interfaces. PLD is particularly useful for producing complex oxide materials and multilayer heterostructures used in magnetoelectric devices. The ability to control film thickness at the nanometer scale makes PLD an essential tool for investigating the fundamental properties of multiferroic materials and designing high-performance devices. Molecular beam epitaxy (MBE) is another advanced deposition technique used to fabricate ultrathin films with atomic-level precision. In this method, beams of atoms or molecules are directed toward a heated substrate under ultra-high vacuum conditions. The atoms condense and arrange themselves on the substrate surface, forming a highly ordered crystalline structure. MBE allows researchers to carefully control film composition, thickness, and interface structure, making it ideal for studying the physics of multiferroic materials and exploring new material systems. Although MBE provides exceptional precision, it is generally more expensive and slower than other fabrication methods, which limits its use mainly to laboratory-scale research. In addition to these techniques, sputtering deposition is widely used in both research and industrial environments for producing multiferroic thin films. Sputtering involves bombarding a target material with high-energy ions in a plasma environment, which ejects atoms from the target and deposits them onto a substrate. This technique offers several advantages, including uniform film deposition over large areas, scalability for industrial manufacturing, and compatibility with semiconductor fabrication processes. Various sputtering methods, such as radio-frequency (RF) sputtering and magnetron sputtering, are commonly used to deposit multiferroic oxide films for electronic applications. Researchers are also exploring nanostructuring and interface engineering techniques to enhance the performance of multiferroic materials. By designing multilayer heterostructures or nanocomposite systems, it is possible to significantly improve magnetoelectric coupling through strain interactions at the interfaces. Advances in thin-film growth technologies and nanoscale fabrication have therefore played a crucial role in enabling the development of high-performance multiferroic devices. Overall, fabrication techniques are a key factor in determining the structural quality and functional properties of multiferroic materials. Continued improvements in synthesis methods and nanofabrication technologies are expected to further enhance the performance and scalability of magnetoelectric devices.

Applications of Multiferroic Materials in Magnetoelectric Devices

Multiferroic materials have attracted considerable attention for their potential applications in next-generation electronic systems due to their unique ability to couple electric and magnetic properties. This magnetoelectric coupling enables new approaches for controlling magnetic states using electric fields, which can significantly reduce energy consumption in electronic devices. As a result, multiferroic materials are being actively explored for use in memory technologies, sensors, spintronic systems, and energy harvesting devices. One of the most promising applications of multiferroic materials is in magnetoelectric random-access memory (MERAM). Traditional magnetic memory technologies require electric currents to switch magnetic states, which leads to energy losses and heat generation. In contrast, MERAM devices utilize electric fields to control magnetic polarization through magnetoelectric coupling. This approach allows information to be written and stored with significantly lower energy consumption. MERAM devices also offer advantages such as non-volatility, fast switching speeds, and high endurance, making them attractive for future data storage technologies. Multiferroic materials are also widely investigated for use in magnetic field sensors. Magnetoelectric sensors exploit the interaction between magnetic and electric properties to detect extremely small magnetic signals. These sensors are capable of converting magnetic field variations into measurable electrical signals with high sensitivity. Applications

of such sensors include medical diagnostics, navigation systems, geophysical exploration, and environmental monitoring. For example, magnetoelectric sensors are being developed for use in biomedical imaging technologies, where they can detect weak biomagnetic signals produced by the human body. Another important application area is spintronics, a rapidly emerging field of electronics that utilizes the spin of electrons in addition to their charge for information processing. Multiferroic materials provide an efficient mechanism for manipulating electron spin using electric fields rather than electric currents. This capability can significantly reduce power
consumption and improve device efficiency. Spintronic devices based on multiferroic materials include spin transistors, spin filters, and spin-based logic circuits, which are expected to play a key role in the development of future computing technologies. Multiferroic materials are also being explored for energy harvesting applications, where environmental energy sources such as mechanical vibrations or magnetic fluctuations are converted into electrical energy. In magnetoelectric energy harvesting systems, magnetic fields induce mechanical strain in magnetostrictive materials, which then generates electric polarization in adjacent ferroelectric materials. This energy conversion mechanism can be used to power small electronic devices, wireless sensors, and Internet of Things (IoT) systems without requiring traditional batteries. Furthermore, multiferroic materials have potential applications in tunable microwave devices and communication systems. The ability to control magnetic properties using electric fields allows for dynamic tuning of microwave components such as filters, phase shifters, and resonators. Such devices could significantly improve the efficiency and adaptability of wireless communication systems. The multifunctional nature of multiferroic materials provides numerous opportunities for developing innovative electronic and magnetoelectric devices. As fabrication technologies continue to improve and new material systems are discovered, multiferroic materials are expected to play a critical role in shaping the future of energy-efficient electronics and advanced information technologies.

Summary

Multiferroic materials represent a rapidly evolving area of materials science with significant implications for next-generation electronic and spintronic technologies. These materials combine multiple ferroic properties within a single system, enabling magnetoelectric coupling that allows electric fields to control magnetic states. Advances in fabrication techniques, material engineering, and nanoscale characterization have significantly improved the understanding and performance of multiferroic materials. Applications such as magnetoelectric memory devices, magnetic sensors, spintronic systems, and energy harvesting technologies demonstrate the transformative potential of these materials. However, challenges related to coupling strength, temperature stability, and scalable fabrication remain key obstacles to commercialization. Continued interdisciplinary research combining materials science, physics, and nanotechnology will play a crucial role in overcoming these limitations. The development of advanced multiferroic materials is expected to contribute significantly to the future of low-power electronics and multifunctional device technologies.

References

[1] Spaldin, N. A., & Fiebig, M. (2005). The renaissance of magnetoelectric multiferroics. Science, 309(5733), 391–392.
[2] Eerenstein, W., Mathur, N., & Scott, J. (2006). Multiferroic and magnetoelectric materials. Nature, 442, 759–765.
[3] Ramesh, R., & Spaldin, N. A. (2007). Multiferroics: Progress and prospects in thin films. Nature Materials, 6, 21–29.
[4] Fiebig, M. (2005). Revival of the magnetoelectric effect. Journal of Physics D, 38(8), R123–R152.
[5] Cheong, S. W., & Mostovoy, M. (2007). Multiferroics: A magnetic twist for ferroelectricity. Nature Materials, 6, 13–20.
[6] Dong, S., Liu, J., Cheong, S. W., & Ren, Z. (2015). Multiferroic materials and magnetoelectric physics. Advances in Physics, 64(5), 519–626.
[7] Hill, N. A. (2000). Why are there so few magnetic ferroelectrics? Journal of Physical Chemistry B, 104(29), 6694–6709.
[8] Bibes, M., & Barthélémy, A. (2008). Multiferroics: Towards a magnetoelectric memory. Nature Materials, 7, 425–426.
[9] Nan, C. W., et al. (2008). Multiferroic magnetoelectric composites. Journal of Applied Physics, 103, 031101.
[10] Scott, J. F. (2012). Multiferroic memories. Nature Materials, 11, 12–13.
[11] Wang, K., Liu, J. M., & Ren, Z. (2009). Multiferroicity: The coupling between magnetic and polarization orders. Advances in Physics, 58(4), 321–448.
[12] Vaz, C. A. F. (2012). Electric field control of magnetism in multiferroic heterostructures. Journal of Physics: Condensed Matter, 24, 333201.