http://www.jourmag.org/index.php/jma

Journal of Magnetism and Its Applications

Received December 26th 2021 received in revised January 9th 2022 accepted January 10th 2022 2022

Research articles

Magnetic Field Effects in Graphene-Based Spintronic Materials

Maria González-Sánchez
Department of Applied Physics, University of Barcelona, Barcelona, Spain

Article info

Keywords:
Graphene spintronics, magnetic field effects, spin transport, magnetoresistance, spin relaxation, spin-orbit coupling, nanomaterials, quantum electronics

Abstract

Graphene has emerged as one of the most promising materials for next-generation spintronic technologies due to its exceptional electrical conductivity, long spin diffusion length, and weak spin–orbit coupling. These properties enable efficient spin transport and manipulation, which are fundamental for developing spin-based electronic devices. Magnetic fields play a critical role in controlling spin polarization, magnetoresistance, and spin relaxation dynamics in graphene-based materials. This study examines the influence of magnetic fields on spin transport phenomena in graphene and graphene-derived heterostructures. It explores mechanisms such as spin injection, spin diffusion, magnetoresistance effects, and spin-orbit coupling modulation under external magnetic fields. Recent experimental and theoretical developments in graphene spintronics are also discussed, highlighting device architectures such as spin valves, magnetic tunnel junctions, and hybrid graphene-ferromagnet systems. The findings demonstrate that magnetic field control can significantly enhance the performance of graphene-based spintronic devices, offering new opportunities for low-power memory systems, quantum information processing, and nanoscale electronics.

1. Introduction

Spintronics, also known as spin-based electronics, represents a rapidly growing field that utilizes the spin of electrons in addition to their charge to process and store information. Unlike conventional electronics, which rely solely on charge transport, spintronic devices exploit spin polarization and magnetic interactions to achieve improved efficiency, faster switching speeds, and reduced power consumption. Graphene, a two-dimensional material composed of a single layer of carbon atoms arranged in a hexagonal lattice, has attracted considerable attention in spintronics due to its unique electronic and magnetic properties. One of the most important advantages of graphene is its extremely high carrier mobility and long spin diffusion length, which allow spins to travel over several micrometers without significant scattering. Additionally, graphene exhibits weak intrinsic spin–orbit coupling and low hyperfine interaction, both of which contribute to prolonged spin coherence times. These characteristics make graphene an excellent platform for studying spin transport and developing advanced spintronic devices. Magnetic fields play a crucial role in graphene spintronics by influencing spin polarization, magnetoresistance, and spin precession. External magnetic fields can control the alignment of magnetic moments in ferromagnetic contacts and modulate spin injection efficiency into graphene layers. Furthermore, magnetic field interactions enable the observation of phenomena such as the Hanle effect, which provides valuable insights into spin relaxation mechanisms and spin diffusion dynamics. Recent advances in material engineering and device fabrication have enabled the integration of graphene with ferromagnetic materials, topological insulators, and transition metal dichalcogenides. These hybrid structures enhance spin-orbit interactions and enable tunable spin transport properties. Understanding how magnetic fields affect these systems is essential for designing next-generation spintronic devices capable of supporting high-density data storage, quantum computing, and ultra-low-power electronic systems.

Fundamental Spin Transport Mechanisms in Graphene (Expanded Discussion)

Spin transport in graphene has attracted significant attention in condensed matter physics and nanoelectronics because graphene exhibits exceptionally long spin diffusion lengths and high carrier mobility. In graphene, electrons can travel several micrometers while preserving their spin orientation, which is a crucial requirement for spintronic applications. This behavior arises from graphene's unique electronic structure, characterized by a linear dispersion relation near the Dirac points and the absence of strong intrinsic spin–orbit coupling. As a result, spin scattering mechanisms are significantly reduced compared with conventional semiconductor materials. The combination of high electrical conductivity and long spin coherence times allows graphene to serve as an efficient medium for transmitting spin information across nanoscale electronic devices. A key process in graphene spintronics is spin injection, where spin-polarized electrons are introduced into the graphene layer from ferromagnetic electrodes. Ferromagnetic materials such as cobalt, nickel, or iron are commonly used as spin injectors because they naturally exhibit unequal populations of spin-up and spin-down electrons. When a current flows from the ferromagnetic electrode into graphene, it carries a net spin polarization that can propagate along the graphene channel. The efficiency of spin injection is strongly influenced by the interface between the ferromagnet and graphene. To improve spin injection efficiency, thin insulating barriers such as magnesium oxide (MgO) or aluminum oxide (Al_2O_3) are often inserted between the electrode and graphene. These tunnel barriers reduce the conductivity mismatch problem and enhance the polarization of injected spins. Once spins are injected into graphene, they diffuse through the material while gradually losing their orientation due to various scattering processes. Spin diffusion is typically described by the spin diffusion equation, which relates the spatial variation of spin polarization to spin relaxation mechanisms. In graphene, spin relaxation occurs primarily through two dominant mechanisms: the Elliott–Yafet mechanism and the Dyakonov–Perel mechanism. The Elliott–Yafet mechanism involves spin flips during momentum scattering events caused by impurities or phonons. In contrast, the Dyakonov–Perel mechanism arises from spin precession in internal effective magnetic fields generated by spin–orbit interactions. Because intrinsic spin–orbit coupling in graphene is relatively weak, the Elliott–Yafet mechanism is often considered the dominant spin relaxation pathway in pristine graphene samples. Magnetic fields play an essential role in controlling spin transport phenomena in graphene. When an external magnetic field is applied perpendicular to the graphene plane, it causes the spins of electrons to precess around the direction of the magnetic field. This phenomenon is known as spin precession and is described by the Larmor precession frequency. As electrons diffuse through the graphene channel, their spins rotate around the magnetic field axis while gradually losing coherence due to scattering processes. The interplay between spin diffusion and spin precession provides valuable insights into the fundamental properties of graphene spin systems. One of the most widely used experimental techniques to study

*Corresponding author
Email: mgonzalez@ub.edu
DOI: 10.53533/JMA.v2i1.27

spin transport in graphene is the non-local spin valve measurement. In this configuration, four electrodes are placed on a graphene sheet: two electrodes are used for injecting spin-polarized current, and two separate electrodes detect the resulting spin signal. Because the detection circuit is physically separated from the charge current path, the measured signal primarily reflects spin accumulation rather than electrical conduction. By switching the magnetization direction of the ferromagnetic electrodes using an external magnetic field, researchers can observe **changes in the detected spin signal. These changes provide direct**

evidence of spin transport across the graphene channel and allow the measurement of spin diffusion lengths. Another important experimental method used to investigate spin dynamics in graphene is Hanle spin precession measurement. In a Hanle experiment, an external magnetic field is applied perpendicular to the graphene surface, causing injected spins to precess while they diffuse through the material. As the magnetic field strength increases, the precession frequency changes, leading to characteristic variations in the detected spin signal. By analyzing the shape of the Hanle curve, researchers can extract key parameters such as spin relaxation time, spin diffusion length, and spin polarization efficiency. These parameters are essential for understanding how effectively graphene can function as a spin transport medium. The study of spin relaxation mechanisms is critical for improving the performance of graphene-based spintronic devices. Spin relaxation occurs when the orientation of electron spins becomes randomized due to interactions with lattice vibrations, impurities, or structural defects. Even though graphene has weak intrinsic spin–orbit coupling, extrinsic factors such as substrate interactions, adatom deposition, and structural disorder can significantly enhance spin scattering processes. For example, graphene placed on certain substrates may experience increased spin–orbit coupling due to proximity effects, which can reduce spin coherence times. Researchers are therefore exploring techniques such as hexagonal boron nitride (h-BN) encapsulation to protect graphene from environmental disturbances and preserve its intrinsic spin transport properties. Magnetic fields can also be used to actively manipulate spin polarization within graphene devices. Strong magnetic fields can align electron spins in a preferred direction, thereby enhancing spin polarization and improving device performance. In addition, magnetic fields can influence magnetoresistance behavior in graphene spin valves by controlling the relative alignment of ferromagnetic electrodes. When the magnetization of the electrodes is parallel, spin-polarized electrons can pass through the graphene channel with minimal scattering, resulting in lower electrical resistance. Conversely, when the magnetizations are antiparallel, spin scattering increases, leading to higher resistance. This magnetoresistance effect forms the fundamental operating principle of many spintronic memory devices. Recent research has also focused on engineering graphene-based heterostructures to enhance spin manipulation capabilities. By combining graphene with materials that exhibit strong spin–orbit coupling, such as transition metal dichalcogenides or topological insulators, researchers can induce new spin-related phenomena. These hybrid structures enable more efficient spin control using both electric and magnetic fields, opening new possibilities for spin-based logic circuits and quantum devices. The continued exploration of magnetic field effects in graphene therefore remains an important area of research for advancing next-generation electronic technologies.

Magnetoresistance Phenomena in Graphene Spintronic Devices (Expanded Discussion)

Magnetoresistance is one of the fundamental physical phenomena that enables the operation of many modern spintronic devices. It refers to the change in electrical resistance of a material when an external magnetic field is applied. In graphene-based spintronic systems, magnetoresistance occurs because magnetic fields influence the alignment of electron spins and the relative magnetization of ferromagnetic electrodes connected to the graphene channel. Since spin-polarized electrons carry both charge and spin information, any change in spin alignment directly affects electrical conduction within the device. This property makes graphene particularly attractive for magnetoresistive applications because its high electron mobility allows spin-polarized currents to travel efficiently across long distances. In graphene spintronic devices, magnetoresistance primarily arises from the interaction between the spin-polarized electrons in graphene and the magnetic orientation of ferromagnetic contacts. These contacts act as spin injectors and detectors that control how electrons enter and exit the graphene channel. When the magnetization of the ferromagnetic electrodes is aligned in a parallel configuration, spin-polarized electrons injected from one electrode can easily travel through the graphene layer and be detected by the second electrode with minimal scattering. This results in a lower electrical resistance state. However, when the magnetization of the electrodes is arranged in an antiparallel configuration, electrons with a particular spin orientation encounter greater resistance because the second electrode favors the opposite spin orientation. As a result, increased scattering occurs, leading to a higher resistance state. The difference between these two resistance states forms the basis of the spin-valve effect. The spin-valve mechanism plays a crucial role in magnetic memory technologies and magnetic sensing systems. In graphene-based spin valves, the graphene sheet acts as a highly efficient spin transport channel that allows spins to propagate over long distances while maintaining coherence. This capability improves the sensitivity and stability of magnetoresistive devices. By applying an external magnetic field, researchers can switch the magnetization direction of the ferromagnetic electrodes, effectively toggling the device between high-resistance and low-resistance states. This switching behavior allows graphene spin valves to function as memory elements in spintronic storage systems. Another important magnetoresistance phenomenon observed in graphene spintronic systems is tunneling magnetoresistance (TMR). TMR occurs when electrons tunnel through an insulating barrier between two ferromagnetic layers. In graphene-based magnetic tunnel junctions, graphene can act as either the conductive channel or part of the tunneling barrier. The probability of electron tunneling depends strongly on the spin alignment of the ferromagnetic electrodes. When the magnetic moments of the electrodes are parallel, tunneling is more likely to occur, resulting in higher electrical conductivity. In contrast, when the electrodes are antiparallel, tunneling probability decreases, leading to increased resistance. Graphene-based magnetic tunnel junctions have demonstrated promising tunneling magnetoresistance ratios due to graphene's atomic thickness and excellent electronic properties. The sensitivity of graphene spin valves to external magnetic fields also makes them highly suitable for magnetic sensing applications. Graphene-based magnetoresistive sensors can detect extremely small variations in magnetic fields, which is valuable for applications such as biomedical imaging, navigation systems, and industrial monitoring. Because graphene exhibits low electrical noise and high thermal stability, sensors based on graphene spintronics can operate reliably under a wide range of environmental conditions. Furthermore, the flexibility and mechanical strength of graphene allow these sensors to be integrated into flexible electronic systems and wearable devices.

Graphene-Based Spintronic Device Architectures (Expanded Discussion)

The development of practical graphene spintronic devices requires carefully designed architectures that allow efficient spin injection, transport, and detection. One of the most widely studied device structures is the graphene spin valve. In this architecture, a graphene sheet serves as the transport channel between two or more ferromagnetic electrodes. The ferromagnetic contacts are typically made from materials such as cobalt, nickel, or permalloy, which provide strong spin polarization. When a current flows through the device, spin-polarized electrons are injected into the graphene channel and propagate toward the detecting electrode. Graphene spin valves are particularly attractive because they combine high electrical conductivity with long spin diffusion lengths. The distance that spins can travel before losing their orientation in graphene can reach several micrometers under optimized conditions. This property allows the design of nanoscale devices capable of transmitting spin information across relatively large distances without significant loss of signal. In addition, graphene spin valves exhibit relatively low power consumption, making them suitable for energy-efficient electronic applications. Another promising device architecture is the graphene-based magnetic tunnel junction. In this configuration, graphene can be integrated as an atomically thin spacer layer between two ferromagnetic materials. Because graphene is only one atom thick, it allows highly controlled electron tunneling processes. Magnetic tunnel junctions with graphene layers have demonstrated improved magnetoresistance performance compared with conventional structures. The unique electronic properties of graphene also enable tunable tunneling behavior, which can be controlled through electric gating or chemical doping. Hybrid heterostructures combining graphene with other two-dimensional materials have also emerged as an important area of research in spintronics. For example, graphene can be stacked with transition metal dichalcogenides such as molybdenum disulfide (MoS_2) or tungsten diselenide (WSe_2). These materials exhibit strong spin–orbit coupling, which can induce spin–orbit interactions in the graphene layer through proximity effects. Such heterostructures enable new mechanisms for controlling spin polarization using electric fields, optical

excitation, or magnetic interactions. The ability to manipulate spins using multiple external stimuli greatly expands the potential functionality of graphene spintronic devices.

Future Prospects and Technological Applications (Expanded Discussion)

The integration of graphene into spintronic systems is expected to significantly influence the future of electronic technologies. One of the most promising applications of graphene spintronics lies in advanced memory systems. Technologies such as spin-transfer torque magnetic random access memory (STT-MRAM) rely on spin-polarized currents to switch the magnetization state of magnetic layers. Because graphene supports efficient spin transport with minimal energy loss, it can improve the performance and durability of such memory devices. Compared with conventional semiconductor memories, spintronic memories offer non-volatility, faster switching speeds, and reduced power consumption. Graphene spintronics may also contribute to the development of next-generation computing architectures. In quantum computing, spin states of electrons can serve as quantum bits (qubits) that store and process information using quantum mechanical principles. The long spin coherence times observed in graphene make it a promising platform for spin-based quantum information processing. Magnetic fields and electric gating techniques can be used to precisely manipulate these spin states, enabling the creation of controllable quantum systems. Another emerging application area is neuromorphic computing, which aims to mimic the structure and operation of the human brain. Spintronic devices based on graphene could be used to create artificial synapses and neurons capable of processing information in a highly parallel and energy-efficient manner. The tunable magnetoresistance properties of graphene spin valves allow them to simulate synaptic weight adjustments, which are essential for learning processes in neural networks. Despite these promising opportunities, several technical challenges remain before graphene spintronics can be widely commercialized. One major challenge is improving the efficiency of spin injection from ferromagnetic electrodes into graphene. The conductivity mismatch between metals and graphene can reduce spin polarization during injection. Researchers are exploring advanced interface engineering techniques and optimized tunnel barriers to overcome this issue. Another challenge involves reducing interface resistance and improving the quality of graphene-ferromagnet contacts. Large-scale fabrication of graphene-based spintronic devices also remains a critical obstacle. While high-quality graphene can be produced using chemical vapor deposition and other synthesis methods, maintaining consistent material quality across large areas is difficult. Defects, grain boundaries, and contamination can significantly affect spin transport properties. Continued advances in materials synthesis, nanofabrication, and device engineering will therefore be essential for translating laboratory research into commercial technologies. Overall, graphene spintronics represents a rapidly evolving field that bridges materials science, condensed matter physics, and electronic engineering. By harnessing the unique properties of graphene and the controllability of magnetic fields, researchers are developing innovative technologies that could transform future computing, sensing, and communication systems.

Summary

Graphene has emerged as a highly promising material for spintronic applications due to its remarkable electrical and spin transport properties. Magnetic fields play a crucial role in controlling spin polarization, spin relaxation, and magnetoresistance in graphene-based systems. Through phenomena such as the Hanle effect and spin valve operation, magnetic fields enable precise manipulation of spin states within graphene devices. Advances in graphene-based heterostructures and device architectures have significantly expanded the potential applications of spintronics, ranging from high-density memory technologies to quantum computing systems. Despite existing challenges related to fabrication and material stability, ongoing research continues to improve device performance and scalability. The study of magnetic field effects in graphene spintronics is therefore essential for developing next-generation electronic technologies that combine high efficiency, low power consumption, and advanced data processing capabilities.

References

[1] Novoselov, K. S., et al. (2004). Electric field effect in atomically thin carbon films. Science.
[2] Han, W., et al. (2014). Graphene spintronics. Nature Nanotechnology.
[3] Roche, S., et al. (2015). Graphene spintronics: The European Flagship perspective. 2D Materials.
[4] Žutić, I., Fabian, J., & Das Sarma, S. (2004). Spintronics fundamentals. Reviews of Modern Physics.
[5] Tombros, N., et al. (2007). Electronic spin transport in graphene. Nature.
[6] Dlubak, B., et al. (2012). Graphene-passivated ferromagnetic electrodes for spin transport. Nature Physics.
[7] Avsar, A., et al. (2020). Colloquium: Spintronics in graphene. Reviews of Modern Physics.
[8] Fert, A., & Jaffrès, H. (2001). Conditions for efficient spin injection. Physical Review B.
[9] Yazyev, O. V., & Helm, L. (2007). Defect-induced magnetism in graphene. Physical Review B.
[10] Awschalom, D. D., et al. (2013). Spintronics and quantum technologies. Science.
[11] Seneor, P., et al. (2012). Spintronics with graphene. MRS Bulletin.
[12] Fabian, J., et al. (2007). Semiconductor spintronics review. Acta Physica Slovaca.